

SAFETY DATA SHEET

PRODUCT CODE: #39

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Silane and Siloxane Penetrating Sealer Water Based
PRODUCT CODES: #39

MANUFACTURER: Epoxy Systems, Inc.
STREET ADDRESS: 20774 West Pennsylvania Ave
CITY, STATE, ZIP: Dunnellon, Florida, 34431

INFORMATION PHONE: 352-489-1666
EMERGENCY PHONE: PERS (USA) 800-633-8253 - (International) +1 (801) 629-0667.
FAX PHONE: 352-489-1625

PREPARED BY: Norm Lambert

DATE REVISED: 3/28/19

Chemical Name or Class: silane/siloxane solution

SECTION 2: HAZARDS IDENTIFICATION

Hazard Overview

GHS Classification: Not classified as dangerous according to the regulations

GHS Label Elements and Precautionary Statements:

Label Elements: None

Hazard Statements:

None

Precautionary statements:

P102 Keep out of reach of children.

P103 Read label before use

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves and clothing to prevent skin contact.

Response:

P302 + P352 IF ON SKIN: wash with plenty of soap and water.

P333 + P313 IF SKIN irritation or rash occurs: Get medical advice/attention.

P321 Specific treatment (see ... on this label).

P362 + P364 take off contaminated clothing and wash it before reuse

Disposal:

P501 Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.

HMIS HAZARD CLASSIFICATION

HEALTH: 1 FLAMMABILITY: 0 REACTIVITY: 0 PERSONAL PROTECTIVE EQUIPMENT: G

POTENTIAL HEALTH EFFECTS

EYES:

MAY CAUSE IRRITATION OR OTHER ALLERGIC RESPONSES.

SKIN:

MAY CAUSE IRRITATION OR OTHER ALLERGIC RESPONSES.

INGESTION:

NONE KNOWN (NOT EXPECTED IN INDUSTRIAL USE)

INHALATION:

MIST MAY SERIOUSLY IRRITATE NOSE, THROAT, AND LUNGS DEPENDING ON CONCENTRATION AND DURATION OF EXPOSURE.

INHALATION OF AEROSOLS OR AMINOFUNCTIONAL SILOXANES MAY CAUSE TOXIC LUNG EFFECTS. NEUROTIC EFFECTS

POSSIBLE, LUNG DAMAGE IS POSSIBLE.

HEALTH HAZARDS (ACUTE AND CHRONIC):

EYE OR SKIN IRRITATION MAY RESULT FROM EXPOSURE. NEUROTOXIC EFFECTS POSSIBLE FROM INHALATION. LUNG

DAMAGE IS POSSIBLE WITH HIGH CONCENTRATIONS OR REPEATED EXPOSURE.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

SENSITIZATION OR POSSIBLE ALLERGIC REACTION CAN BE CAUSED BY REPEATED EXPOSURE.

CARCINOGENICITY

OSHA: NO NTP: NO IARC: NO

ADDITIONAL CARCINOGENICITY INFORMATION:

RE: Ethanol (CAS# 64-17-5): carcinogenicity: A4 (ACGIH)

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

<u>INGREDIENT</u>	<u>CAS NO.</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>OSHA STEL</u>	<u>WEIGHT %</u>
ALCOHOL POLYGLYCOL ETHER	9043-30-5	NONE	NONE	NONE	10-30
OCTYL TRIETHOXY SILANE	35435-21-3	NONE	NONE	NONE	10-30

SAFETY DATA SHEET

PRODUCT CODE: #39

WATER	7732-18-5	NONE	NONE	NONE	30-60
*ETHANOL (as a hydrolysis byproduct)	64-17-1	1000ppm	1000ppm	NONE	varies

TOXIC CHEMICAL(S) SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III AND OF 40 CFR 372 ARE PRESENT.

Note: Ingredients listed without percentages, the percentages are considered a trade secret.

SECTION 4: FIRST AID MEASURES

EYES:

IMMEDIATELY FLUSH EYES WITH WATER FOR 15 MINUTES AND SEEK MEDICAL ATTENTION.

SKIN:

FLUSH SKIN IMMEDIATELY WITH WATER FOR 15 MINUTES AND SEEK MEDICAL ATTENTION IMMEDIATELY IF NECESSARY.

INGESTION:

INDUCE VOMITING AND SEEK MEDICAL ATTENTION. ALLOW VICTIM TO DRINK AS MUCH COLD WATER AS POSSIBLE.

INHALATION:

REMOVE TO FRESH AIR AND RECEIVE MEDICAL ATTENTION IF ILL EFFECTS PERSIST.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:

SECTION 5: FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS IN AIR, UPPER: not available
(% by volume) LOWER: not available

FLASH POINT: ° F >200

METHOD USED:

SETA FLASH

EXTINGUISHING MEDIA:

FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIRE FIGHTING PROCEDURES:

SELF CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING SHOULD BE WORN IN FIGHTING FIRES INVOLVING CHEMICALS.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

VAPORS ARE HEAVIER THAN AIR AND CAN TRAVEL ALONG THE GROUND TO IGNITION SOURCES.

SECTION 6: RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

WEAR APPROPRIATE SAFETY EQUIPMENT WHEN HANDLING MATERIAL. DIKE MATERIAL AND TAKE UP WITH ABSORBANT TO SALVAGE CONTAINER.

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

WEAR SUITABLE PROTECTIVE CLOTHING TO AVOID CONTACT WITH MATERIAL. WEAR NEOPRENE OR RUBBER GLOVES. WEAR SPLASH GOGGLES WITH SIDE SHIELDS. STORE AWAY FROM HIGH HEAT, CONTACT WITH FLAMES AND/OR SPARKS. KEEP MATERIAL IN SEALED CONTAINERS THAT ARE PROPERLY LABELED. DO NOT ALLOW MATERIAL TO FREEZE.

OTHER PRECAUTIONS:

USE GENERAL SAFETY PRECAUTIONS WHEN USING THIS MATERIAL. WASH HANDS BEFORE USING TOILET FACILITIES.

REMOVE CONTAMINATED CLOTHING PROMPTLY.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION:

USE A SUITABLE NIOSH APPROVED RESPIRATOR UNLESS ADEQUATE VENTILATION IS PROVIDED. AVOID THE INHALATION OF ANY MISTS THAT MAY BE GENERATED IN THE APPLICATION PROCESS.

VENTILATION:

PROVIDE FOR ADEQUATE GENERAL AND LOCAL VENTILATION TO PREVENT EXCEEDING LEVELS AS PRESCRIBED BY LAW.

PROTECTIVE GLOVES:

RUBBER OR NEOPRENE

EYE PROTECTION:

SPLASH GOGGLES WITH SIDE SHIELDS.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

PROVIDE NECESSARY CLOTHING AND SAFETY EQUIPMENT TO PREVENT CONTACT WITH MATERIAL.

WORK HYGIENIC PRACTICES:

SEE SECTION THREE FOR OCCPATATIONAL EXPOSURE LIMIT VALUES.

SAFETY DATA SHEET

PRODUCT CODE: #39

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: TRANSPARENT WHITE OR COLORLESS LIQUID WITH SLIGHT ODOR
BOILING POINT OR RANGE: ° F - 212
VAPOR DENSITY (AIR = 1): N/A
SPECIFIC GRAVITY (H₂O = 1): 1.0
EVAPORATION RATE: N/A
SOLUBILITY IN WATER: SOLUBLE

Odor Threshold: N/A
pH: N/A
Melting point/freezing point: N/A
Vapor Pressure: N/A
Auto Ignition Temperature: N/A
Partition Coefficient: n-octanol/water: N/A
Decomposition Temperature: N/A

SECTION 10: STABILITY AND REACTIVITY

STABILITY:
STABLE
CONDITIONS TO AVOID (STABILITY):
NONE KNOWN
INCOMPATIBILITY (MATERIAL TO AVOID):
AVOID CONTACT WITH OXIDIZING MATERIALS
HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:
CARBON OXIDES AND TRACES OF INCOMPLETE CARBON COMPOUNDS, SILOCON DIOXIDE (HIGH HEAT), METAL OXIDES, AND FORMALDEHYDE
HAZARDOUS POLYMERIZATION:
WILL NOT OCCUR

SECTION 11: TOXICOLOGICAL INFORMATION

Toxicological testing has not been performed with this material. Primary Irritation to eyes – not irritating (rabbit) – Conclusion by analogy.

SECTION 12: ECOLOGICAL INFORMATION

No ecological data exists for this product. The hydrolysis by product (Ethanol) is readily biodegradable, silicone content is not biologically degradable. Bioaccumulation is not expected to occur. According to past experience, toxicity to fish is improbable.

SECTION 13: WASTE DISPOSAL

WASTE DISPOSAL METHOD:
DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.

SECTION 14: Transport Information

DOT: Not Regulated

IMO/MDG: Not Regulated

SECTION 15: REGULATORY INFORMATION

All components are on the TSCA list. This Material Does not contain any OSHA or WHIMS reportable hazardous ingredients. All components are on the AICS, EINECS, ECL, ENCS and Canada DSL lists. WHIMIS hazard class: None.
Product (as a byproduct of hydrolysis) may generate ethanol (CAS# 67-55-1), which is a Hazardous air pollutant (HAP).

SECTION 16: OTHER INFORMATION

DISCLAIMER: The information Contained herein is based on the data available and is believed to be accurate, However, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.

N/A = Not Available
See Section 1 for date of preparation